EP5555T

55" Dual Screen
WITH One Side TOUCH

Interactivity Meets Advertising

In-store "Way-finding" is easy with ViewSonic's new interactive ePoster display solution. With its drift free 4K x 4K touch interface and vivid screen resolution, retail messaging and image navigation is easy with all-in-one eP5555T ePoster. Simple connect the output of your PC to the versatile input ports and common USB port for your touch interface and your application comes alive. ViewSonic's ePoster display can easily be connected to a corporate network by adding a network media player. Security is achieved through the locking back cover.

- **Dual screen 55" full HD ePoster featuring 1920x1080 resolution and tempered glass faceplate for screen protection**
- **Interactive built-in "one-point" IR touch panel features 4096x4096 touch resolution for accurate selection of data**
- **All-in-One design provides easy customer deployment with no required construction**
- **Dual Internal RISC media player with 2GB CF storage for playing JPEG images and digital video files**
- **Built-in power outlet and mounting cradle for adding your own media player**
- **Applications:**

RETAIL ADVERTISING
WAY-FINDING
HOSPITALITY
EDUCATION

ViewSonic®
See the difference®

EP5555T 55" DIGITAL SIGN BOARD WITH INTERACTIVE TOUCH





DISPLAY	Diagonal	55" (139.7 cm)
	Resolution	1920x1080 pixel resolution
	Color	Over 16.7M color (depending on video card used)
	Brightness	450 cd/m^2 (typ)
	Contrast Ratio	5000:1 (typ)
	Response Time	6.0ms (typ gray-to-gray)
	View Angle	Up and down 178°, left and right 178° (typ) @ CR>10
TOUCH SCREEN	Touch Mode	One point click, long press right click, double click, draw
	Resoltuion	4096x4096 dots
	Response Time	8ms
	Supports OS	Windows® 7/2000/XP/Vista
	Interface	USB 2.0 (full speed), USB 1.1 port HID compliant
CONNECTIVITY	I/O Ports	HDMI, VGA, YPbPr, USB (x3), A/V, RJ45 Pigtail
INTERNAL	Storage	2GB CF card
	Media Player Supports	Video: MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4 Photo: JPEG Audio: WMA, MP3, M4A (AA CC)
		Clock and timer
AUDIO	Speakers	5W (x2)
POWER	Supply	3.2–1.38 A @ 100–240VAC, 50/60Hz
	Consumption	900W (max)
	Save	Off < 1W
OPERATING CONDITIONS	Temperature	32–104° F (0–40° C)
	Humidity	20–90% (non-condensing)
STORAGE ENVIRONMENT	Temperature	-4–140° F (-20–60° C)
	Humidity	10–90% (non-condensing)
DIMENSIONS (WxHxD)	Physical	32.68" x 76.77" x 18.31" (830mm x 1950mm x 465mm)
WEIGHT	Net	352.7 lbs. (160 kg)
	Gross	396.8 lbs. (180 kg)
REGULATIONS		FCC, ICES 003, CE
MTBF		50,000 hrs.
PACKAGE CONTENTS		ePoster, power cord, remote control with batteries, key, Quick Start Guide, User Manual and Software on CD
WARRANTY		1-year with extended options available



1 – 1920x1080 Resolution
2 – Security Latch/Handle
3 – RJ45 Ethernet LAN port (extension to optimal media player)
4 – 3x USB 2.0 Ports
5 – 2GB CF Card Storage
6 – HDMI Port
7 – VGA Input
8 – YPbPr/Composite Video/Audio
9 – PC Audio
10 – USB Port
11 – AC Power Male Port
12 – AC Power Female Port
13 – Power On/Off

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15969-00B-05/11] EP5502T-1

ViewSonic® See the difference®

For more product information, visit us on the web at ViewSonic.com